

# **TECHNICAL DATASHEET NACRITE S1P**

Ref. 9NACL10 Sizes 35 >> 48 INDOOR LOW SHOE LOW SHOES S1P SRC The -Value for money Reflective stripe . PU2D injected outsole Defined heel . PURCHASE PACKAGING REF. EU US 9NACL10035 35 3 9NACL10036 36 4 4.5 9NACL10037 37 9NACL10038 38 5.5 9NACL10039 39 6 9NACL10040 40 7 8 9NACL10041 41

## DESCRIPTION

NACRITE S1P is a low shoe that features an upper made of leather and polyurethane with a lining made of mesh. Its dual density PU/PU sole resists to hydrocarbons and to slip on ceramic and steel floors. It provides comfort to user. The reflective insert at the back improves safety of wearer when working in dark environment. This model is equipped with a steel toe-cap and a steel plate for protection against puncture and fall of heavy objects.

NACRITE is the right model for any indoor use or in dry environment.

### SECTORS

### **Service**

Second work

Infrastructure, building industry

**Transport and logistics** 

## **APPLICATIONS EXAMPLES**

- Painter,
- Electrician,
- Storekeeper, ...

# See also

9NACL10042

9NACL10043

9NACL10044

9NACL10045

9NACL10046

9NACL10047

9NACL10048



555 rue de la Dombes, 01700 Miribel - Tél. : +33 4 72 26 57 57

42

43

44

45

46

47

48

8.5

9.5

10

11

11.5

12.5

13.5

47

10

10

10

10

10

10

10

10

10

10

10

10

10

10



# **NACRITE S1P**

## **TECHNICAL FEATURES**

Closure	Lacing	Anti perforation sole	Stainless less
Тое сар	Steel	Reflective trim	Reflective trim at the back
Work environment	Indoor	Examples of applications	Painter, Electrician, Storekeeper, …
Sub-family	Low shoe	Color	Black
Upper	Action leather and PU	Insole	Removable, textile and foam
Loops	Metal eyelets	Midsole	Injected polyurethane
Wearing sole	Polyurethane	Main assembly	Injected assembly
Lining	Moisture wicking non-woven		

### INSTRUCTIONS FOR USE AND STORAGE

Instructions for use :

- These shoes can be perfectly preserved. Before any use, effect of a visual inspection is perfect. It is advisable to choose the appropriate model for the specific requirements of your workplace.

#### Storage instructions :

- Place the shoes, when not in use, in a dry, clean and airy place. The time influences all materials and even if only first class raw materials have been used, storage for longer than 3 years is not recommended.

#### Cleaning instructions :

- Regularly clean the shoes by using brushes, cleaning clothes.

### LEGISLATION

This shoe conforms to the personal protective equipment model covered by the EC type-examination certificate 0075/1747/161/05/19/1523 EXT 01/04/20. Delivered by CTC (0075).



S1P SRC

S1P : Closed heel, antistatic shoe, fuel and oil resistant contact outsole, energy absorbing heel, puncture resistant midsole, resistant to a 1 100 Newtons pressure
SRC : Slip resistant outsole on ceramic or steel floor with dilute soap solution or glycerol

PPE CAT. I

Minor risks (auto-certification)

Retailer stamp

UPDATE 04/09/2020