

# FIREMAN SABF Boots



## Reference: FIREMAN SABF Boots (safety toe cap + anti-perforation mid-sole)

Excellent resistance to heat flow, heat contact, fire.

Excellent resistance to chemicals : fuels, oils, weak and diluted acids, solvents.

Excellent resistance to abrasion and cuts

Used with chemical protective suits (satisfy permeation tests according to EN 943-1 and EN 943-2).

## Comply with standards :

### EN 15090 type 3 HI3

Boots for emergency situation and fire with toxic chemicals emission.

### EN ISO 20345 S5 HRO SRC

- Heel shock absorption.
- Antistatic.
- Resistance to heat contact (HRO).

### EN 13832-3 J P Q

- Boots highly resistant to chemicals :
- N-Heptane (J)
- Hydrogen peroxide (P)
- Isopropanol (Q)

### EN 13287

- Sole slip resistance (SRC) :
- Steel floor.
- Ceramic floor.

Marine fire protection equipment certified by BG VERKEHR, notified body N°0736 .

\* Sizes 3 and 4.5 have steel toe cap and steel midsole.

## Colors

Black



ATS sole  
(registered  
design)

Anti-perforation  
+ Safety toe  
cap

Polymer toe cap\*

Composite anti-perforation  
mid-sole\*

Outside height (size 8): 370  
mm

Weight (size 8): 2100g / pair

Elastomer: fireproofed NBR /  
CR

(fireproofed  
nitrile/polychloroprene rubber)

## Sizes

FR	36	37/38	39	40/41	42	43	44	45	46/47	48	49/50
UK	3	4.5	5.5	7	8	9	9 ½	10 ½	11 ½	13	14

Please contact us for sizes 3 and 4.5 certificate.

---

### Available options

---



**R : Mid-boot reflective band** **AC2 : Leather straps**



[www.etchesecurite.com](http://www.etchesecurite.com) | ZA Ordokia - 64130 VIODOS - ABENSE de BAS - FRANCE |

+33 (0)5 59 28 05 41