

NEOPRENE SA Boots



Reference: NEOPRENE SA Boots (safety toe cap + anti perforation mid-sole)

- Excellent resistance to acids, fuels and solvents.
- Excellent resistance to abrasion and cuts.
- For use with protective clothing in hostile environments.

Comply with standards :

EN ISO 20345 S5 HRO CR SRC

- Heel energy absorption.
- Antistatic.
- Contact heat resistance (HRO)
- Cut resistance (CR)

EN 13832-3 J Q R

Boots highly resistant to chemicals :

- N-Heptane (J)
- Isopropanol (Q)
- Sodium Hypochlorite(R)

EN 13287

Sole slip resistance (SRC) :

- Ceramic floor.
- Steel floor.

* made of steel for sizes 3 and 4,5.

Colors

Black



ATS sole
(registered
design)

Anti-perforation
+ Safety toe
cap

Polymer toe cap*

Composite anti-perforation
mid-sole*

Outside height for size 8: 370
mm

Weight for size 8: 2200g / pair

Elastomer: CR (Neoprene**)

** DuPont Performance
Elastomer patented

Sizes

FR	36	37/38	39	40/41	42	43	44	45	46/47	48	49/50
UK	3	4.5	5.5	7	8	9	9 ½	10 ½	11 ½	13	14

Please contact us for sizes 3 and 4.5 certificate.



www.etcheseurite.com | ZA Ordokia - 64130 VIODOS - ABENSE de BAS - FRANCE |

+33 (0)5 59 28 05 41

