

QUALITY CERTIFICATE

OUTDOOR Stainless Steel Convex Mirrors									
SIZE (mm)		320	490	600	800	1000	1000	450x600	600x800
PRODUCT CODE		CMCL162532NH00	CMCL172749NH01	CMCH1529605CE0	CMCH1529805CE0	CMCHB820A05CE0	CMCH1820A05CE0	CMRH192946SCE0	CMRH192946SCE0
LENS	MATERIAL TYPE	SUS 304	SUS 304	SUS 304	SUS 304	SUS 201	SUS 304	SUS 304	SUS 304
	THICKNESS (MM)	0.6	0.7	0.5	0.5	0.8	0.8	0.9	0.9
	TOLERANCE	+/- 0.05	+/- 0.05	+/- 0.05	+/- 0.05	+/- 0.05	+/- 0.05	+/- 0.05	+/- 0.05
REFLECTIVITY	PERCENTAGE	> 60%	> 60%	> 60%	> 60%	> 60%	> 60%	> 60%	> 60%
RADIUS	R'	650	1200	2200	3000	3600	3600	2200	3000
	TOLERANCE	+/- 5%	+/- 5%	+/- 5%	+/- 5%	+/- 5%	+/- 5%	+/- 5%	+/- 5%
EFFECTIVE VIEWING AREA	TOLERANCE	- 20 MM	- 20 MM	- 30 MM	- 30 MM	- 30 MM	- 30 MM	- 30 MM	- 30 MM
	RANGE (L-U)	300~320	470~490	570~600	770~800	970~1000	970~1000	570~600 (X) 420~450 (Y)	770~800 (X) 570~600 (Y)
BACK PLATE	MATERIAL TYPE	SUS 430	SUS 430	SGCC-Z	SGCC-Z	SGCC-Z	SGCC-Z	SGCC-Z	SGCC-Z
	THICKNESS (MM)	0.5	0.7	0.9	0.9	1.0	1.0	0.9	0.9
	TOLERANCE	+/- 0.05	+/- 0.05	+/- 0.05	+/- 0.05	+/- 0.05	+/- 0.05	+/- 0.05	+/- 0.05
UNIT WEIGHT REFERENCE	KG	2.0	4.0	8.50	11.5	19.5	19.50	8.5	13.5
SET BRACKETS	TYPE	ALUMINIUM ALLOY 6063	ALUMINIUM ALLOY 6063	MILD STEEL MATERIAL	MILD STEEL MATERIAL	MILD STEEL MATERIAL	MILD STEEL MATERIAL	MILD STEEL MATERIAL	MILD STEEL MATERIAL
	COATING	-	-	HOT-DIP GALVANIZERS (HDG)	HOT-DIP GALVANIZERS (HDG)	HOT-DIP GALVANIZERS (HDG)	HOT-DIP GALVANIZED	HOT-DIP GALVANIZERS (HDG)	HOT-DIP GALVANIZERS (HDG)
SIZE BRACKET AVAILABLE (TUBE DIAM. Φ)	MM	50	50	60 or 76	60 or 76	60 or 76	60 or 76	60 or 76	60 or 76
WEIGHT BRACKETS	KGS	Inc.	Inc.	60 Φ = 1,12 76 Φ = 1,25	60 Φ = 1,12 76 Φ = 1,25	60 Φ = 1,12 76 Φ = 1,25	60 Φ = 1,12 76 Φ = 1,25	60 Φ = 1,12 76 Φ = 1,25	60 Φ = 1,12 76 Φ = 1,25

1. Sun Cap: Orange UV Resistance Polycarbonate (Round Mirrors); Orange Stainless Steel Sheet (Rectangular Mirrors)
2. Protective Ring: Orange UV Resistance PVC Material

Indicative data, subject to possible unilateral changes. The weight is indicative and not binding.