

# FOLDING SINGLE USE MASK FFP1D WITH VALVE

Ref. 23105

TECHNICAL SHEET



## MEASUREMENTS

Superior part width (mm)	85
Inferior part width (mm)	20
Height (mm)	87
Pince-nez (mm)	90x90x0.5 (L x l x E)
Valve (mm)	41 x 11 (D x h)
Elastic (mm)	560 x 0.7 x 6 (L x E x l)

## GENERAL DESCRIPTION AND MATERIALS

- **Single use** protection mask **FFP1D SL**
- **Folding**
- Filter Media : High Filtration Efficiency Melt-Blown (polypropylene)
- Natural rubber elastic
- Outer, inner and support layers in a **polypropylene**
- Polyethylene encapsulated iron wire pince-nez
- Valve in **polypropylene and synthetic rubber**

## SPECIFIC ADVANTAGES

- Allergic test
- Expiration valve
- Hygienic

## MAIN APPLICATION FIELDS

- Protection against non toxic solid and liquid for concentrations **up to 4xOEL**
- **Do not use in a place where oxygene concentration is less than 17 % vol.**
- Against calcium carbonate, chia clay, cement, cellulose, sulfur, cotton, flour, carbon, ferrous metals, vegetable oils and soft woods
- Textil industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork (strong woods except)

## PACKAGING

- **Individual** packing
- **240 masks** in a box
- 20 masks in a bag

## STANDARDIZATION

This mask is in conformity with the model of individual safety equipment which correspond to

**The CE Type-examination certificate 59765**

Delivered by **BSI (notified body n° 0086)**

**EN 149 : 2001**

This mask is in conformity with the « French JO notice » 135 from 06/12/04.



**SACLA** – Z.I. de Rosarge – 01700 LES ECHETS – MIRIBEL – FRANCE

Tél. : (33) 04 72 26 57 57 – Fax. : (33) 04 72 26 51 70 – Mail : [contact@sacla-tm.fr](mailto:contact@sacla-tm.fr)