

SINGLE USE MASK FFP1D SL WITH VALVE

Ref. 23106

TECHNICAL SHEET



MEASUREMENTS

Mask (mm)	139 x 127 x 54 (L x W x H)
Nose cushion (mm)	100 x 27 x 1.5 (L x W x T)
Pince-nez (mm)	90 x 5 x 0.5 (L x W x T)
Sup. elastic (mm)	300 x 5 x 0.55 (L x W x T)
Inf. elastic (mm)	265 x 5 x 0.55 (L x T x W)
Valve (mm)	41 x 11 (D x H)
Weight	12 g

GENERAL DESCRIPTION AND MATERIALS

- **Single use** protection mask **FFP1D SL**
- Filter Media : High Filtration Efficiency Melt-Blown (polypropylene)
- Synthetic rubber elastic **without latex**
- **Valve in polypropylene and synthetic rubber**
- Outer layer in **polypropylene**
- Inner layer in **polyester**
- **Aluminium** pince-nez
- Nose cushion in **polyethylene foam**

SPECIFIC ADVANTAGES

- Allergic test
- Without latex
- Hygienic
- Valve

MAIN APPLICATION FIELDS

- Protection against non toxic solid and liquid aerosols for concentration **up to 4xOEL**
- **Do not use in a place where oxygen concentration is less than 17 % Vol.**
- Against calcium carbonate, china clay, cement, cellulose, sulfur, cotton, flour, carbon, ferrous metals, vegetable oils, soft woods
- Textile industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork (strong woods except)

PACKAGING

- 10 masks in a bag
- **120 masks** in a box

STANDARDIZATION

This mask is in conformity with the model of individual safety equipment which correspond to

The CE Type-examination certificate 59765

Delivered by **BSI (notified body n° 0086)**

This mask is in conformity with the « French JO notice » 135 form 06/12/04.

EN 149 : 2001



SACLA – Z.I. de Rosarge – 01700 LES ECHETS – MIRIBEL – FRANCE

Tél. : (33) 04 72 26 57 57 – Fax. : (33) 04 72 26 51 70 – Mail : contact@sacla-tm.fr