FOLDING SINGLE USE MASK WITH VALVE FFP3D SL

Ref. 23305

TECHNICAL SHEET

MEASUREMENTS

MasK (mm)	Inferior part width : 85 Superior part width : 200 Height : 87
Pince-nez (mm)	90 x 9 x 0.5 (L x W x T)
Elastic (mm)	560 x 0.7 x 6 (L x T x W)
Valve (mm)	41 x 11 (D x H)

GENERAL DESCRIPTION AND MATERIALS

• **Single use** protection mask FFP3D SL

• Foldable, with valve

• Outer, inner and support layers in **polypropylene**

• Filter media : High Filtration Efficiency Melt-Blown (polypropylene), eletrostatic

• Polyethylene encapsulated iron wire pince-nez

• Natural rubber elastic

• Valve housing in polypropylene and valve membrane in synthetic rubber

SPECIFICAL ADVANTAGES

• Allergic test

• Expiration valve

• Resistant

• Fireproof

MAIN APPLICATION FIELDS

• Against toxic solid and liquid aerosols up to 50xOEL

• Textile industry, craft industry, metallurgical industry, mining industry, underground civil engineering, woodwork, welding, melting, metal cutting out, hospitals, laboratories, medical controls, pharmaceutical industry, toxical waste treatment, batteries making (Ni-Cad)

• Against calcium carbonate, china clay, cement, cellulose, sulfur, cotton, flour, carbon, ferrous metals, harwood, glass fibers, plastic, vegetable oils and mineral oils, quartz, copper, aluminium, bacteria, fungi and mycobacterium tuberculosis, chromium, manganese, nickel, platinum, strychnine, metal dust and smoke, viruses and enzymes

• **Do not use in a place where oxygene concentration is less than 17 % Vol.**

PACKAGING

• **Individual** packing

• **240 masks** in a box

• 20 masks in a bag

• Distributor box

STANDARDIZATION

This mask is in conformity with the model of individual safety equipment which correspond to

The CE Type-examination certificate 59765

Delivered by **BSI (notified body n° 0086)**

This mask is in conformity with the **French JO notice** 135 from 12th June 2004.

EN 149 : 2001

$C\epsilon$