NITRILE COATED KEVLAR® GLOVES

Ref.9660 (9659)



SIZES AND REFERENCES

Size	Ref.	Bar code
9	9659	3435241096593
10	9660	3435241096609







DESCRIPTION AND MATERIALS

- Kevlar® palm
- Open cotton back
- Double blue nitrile coating

- PVC cuff, 7 cm
- Superior quality

SPECIFIC FEATURES

- Good cut resistance
- Resistance to heat up to 100°C

- Grip
- · Reinforced solidity

MAIN APPLICATION FIELDS

- Heavy handling
- · Ordinary and mechanical tasks

- Handling of skidding or oily products
- · Engineering, woodwork, building

PACKING

• Packed by 10 pairs

• 100 pairs in a carton

STANDARDS


This glove is in conformity with the prototype of personal protective equipement which corresponds to

EC Type-examination certificate N° GB09/77879

Issued by SGS (notified body n° 0120)

EN 420:2003

EN 388:2003



- Abrasion = 4/4
- **Blade cut** = 4/5
- **Tear** = 3/4
- Puncture = 2/4

 $C \in$

EN 407:2004



- Resistance to flammability = X
- Resistance to **contact heat** = 1/4
- Resistance to **convective heat** = X
- Resistance to radiant heat = X
- Resistance to small splashes of molden metal = X
- Resistant to large splashes of molden metal = X